



## 077 117 03 726 | anthracite

MP 860 | single sided  
pathway luminaire  
LED | 14 W 3000 K



- pathway luminaire MP 860 single sided
- with anti.glare reflector system to limit glare
- the luminaire generates an homogenous "carpet of light"
- for mounting on ground with sufficient load bearing capacity or with socket (sold separately)
- with LED 2000 lm
- colour temperature: 3000 K
- colour rendering index: CRI >90
- L85 / B10 (50.000h / ta 25°C)
- SDCM < 2
- net luminous flux: 390 lm
- total load: 14 W
- luminous efficacy: 27,9 lm/W
- asymmetrical light distribution
- single sided light output
- reflector of aluminium, silver anodised
- with built in LED power unit, electronic, 220-240 V, 50/60 Hz
- power supply: supply cord, H07RN-F 3x1,5 mm<sup>2</sup>
- housing of cast aluminium
- safety glass, clear
- length: 295 mm, width: 239 mm, height: 860 mm
- weight: 14,5 kg
- protection rating: IP65
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- maximum ambient temperature: 50 ° C
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: anthracite
- 077 117 03 726

- Overview of accessories on the following page / s

077 117 03 726  
**accessory****Optional accessories**

description accessory general	dimensions in mm	item number	pic.-No.
underground socket for pathway luminaires MP 860	ØxH: 236 x 600	101100	01
connection sleeve IP68 for ground recessed luminaire	ØxL: 26,5 x 116	071 212 00 000	02

