



## 14L3250AMCE916 | silver

14L  
projector  
LED Amber | 250 W

LED

DMX

IP65

III

IK08

CE

5Y

- projector 14L
- for wall-, ground and ceiling mounting
- power supply and mounting bracket must be ordered separately
- with LED Amber
- L80 / B10 (50.000h)
- SDCM < 3
- total load: 250 W
- rotationsymmetrical light distribution, flood
- beam angle: 32 °
- for external power supply, integrated control unit (DMX)
- 48V DC
- control ON/OFF, DMX
- secondary connection:
- connecting terminal in cutting/terminal technology (type: for H05 RN-F 4 x 0,75-1,5 with tightening range diameter 7-10 mm, DMX cross section range of the cores 0,34-0,75 mm<sup>2</sup>)
- housing of die cast aluminium
- safety glass, clear
- length: 328 mm, width: 429 mm, height: 464 mm
- windage area: 0,15 m<sup>2</sup>
- weight: 9,823 kg
- protection rating: IP65
- protection class III
- 5 years warranty
- impact resistance class: IK08
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: silver (RAL9006)
- 14L3250AMCE916

- Overview of accessories on the following page / s

14L3250AMCE916

**accessory****Required accessories**

description accessory general	dimensions in mm	item number	pic.-No.
LED power unit IP67, 48V / 320W for projector 14L for outdoor usage	LxWxH: 251 x 90 x 44	814L25000	01
Edged bracket for projector 14L		814L0010B916	02
Pivoting bracket for projector 14L		814L0010H916	03
Standard bracket for projector 14L		814L00100916	04

**Optional accessories**

description accessory general	dimensions in mm	item number	pic.-No.
Screen 45° for projector 14L		814L00545916	01

