
HOFFMEISTER





LED 2700 K		K 610lm	⊄ 17°
h	CI		Em
[m]	Ø[m		[lx]
1.0	0.31		2000
2.0	0.5		500
3.0	0.89	-	222
4.0	1.18		125
5.0	1.48	8	80

035 061 02 908 D I chrome

DL 70 | LED downlight LED COB | 10 W 2700 K



- downlight DL 70 LED
- with a rim projecting over the ceiling with LED COB 920 lm
- colour temperature: 2700 K
- colour rendering index: CRI >90
- L80 / B10 (50.000h)
- SDCM < 2
- net luminous flux: 610 lm
- total load: 10 W
- luminous efficacy: 61,0 lm/W rotationsymmetrical light distribution, medium
- reflector of highest grade aluminium 99.9%, mirror finish anodised - cut of angle: 30 °
- UGR: 13
- with external LED power unit, electronic (DALI), 220-240 V, 0/50/60 Hz
- power supply: supply cord with free conductor end 2x0,75 mm², length: 200 mm
- housing of aluminium and die cast aluminium
- height: 73 mm
- diameter: 100 mm, recessing diameter: 83 mm recessing depth: 73 mm, ceiling thickness: 4-25 mm
- weight: 0,22 kg
- protection rating: IP20 IP44 in closed ceiling systems
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: chrome
- 035 061 02 908 D