





## 108 324 04 910 RD | white

complx.200 | rim  
directional spotlight  
LED | 26 W 4000 K



- directional spotlight complx.200 rim
- with a rim projecting over the ceiling
- for installation into suspended ceilings
- with LED 2500 lm
- colour temperature: 4000 K
- colour rendering index: CRI >80
- L90 / B10 (50.000h)
- SDCM < 2
- net luminous flux: 1980 lm
- total load: 26 W
- luminous efficacy: 76,2 lm/W
- rotationsymmetrical light distribution, narrow spot
- aluminium darklight reflector, mirror finish anodized
- safety-rope for reflector modules
- beam angle: 5 °
- with external LED power unit, electronic (DALI), 220-240 V, 0/50/60 Hz
- temperature-controlled LED circuit board (NTC)
- dimmable
- dimming range: 100-1 %
- power supply: supply cord with plug connection 2x5x2,5 mm², length: 360 mm
- housing of die cast aluminium
- safety glass, clear
- recessing ring of die cast aluminium
- height: 175 mm
- diameter: 230 mm, recessing diameter: 220 mm
- recessing depth: 190 mm, ceiling thickness: 1-35 mm
- rotatable 360°, fixable setting, 0°-30° tilttable, fixable setting
- weight: 2,36 kg
- protection rating: IP20
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: white (RAL9016)
- 108 324 04 910 RD

---