





108 732 04 910 P | white

complx.100 | insider
directional spotlight
LED | 14 W 4000 K



- directional spotlight complx.100 insider
- with plasterboard panel and integrated installation frame
- with LED 1560 lm
- colour temperature: 4000 K
- colour rendering index: CRI >80
- L90 / B10 (50.000h)
- SDCM < 2
- net luminous flux: 1270 lm
- total load: 14 W
- luminous efficacy: 90,7 lm/W
- rotationsymmetrical light distribution, spot
- safety cable for reflector module
- reflector of aluminium, mirror finish anodised
- beam angle: 15 °
- with external LED power unit, electronic, 220-240 V, 50/60 Hz
- Dimming with external dimmers possible (trailing-edge and leading-edge)
- dimmable
- power supply: supply cord with plug connection 2x5x2,5 mm², length: 360 mm
- housing of die cast aluminium
- safety glass, clear
- recessing ring of die cast aluminium
- length: 400 mm, width: 400 mm, height: 127 mm
- diameter: 102 mm
- recessing depth: 137 mm, ceiling thickness: 12.5 mm
- rotatable 360°, fixable setting, 0°-30° tilttable, fixable setting
- weight: 1,9 kg
- protection rating: IP20
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: white (RAL9016)
- 108 732 04 910 P
