
HOFFMEISTER







LED 4	<469°	
h	CO	Em
[m]	Ø[m]	[lx]
1.0	1.37	683
2.0	2.75	171
3.0	4.12	76
4.0	5.50	43
5.0	6.87	27

108 742 04 910 R I white

complx.100 | rim ceiling recessed luminaire LED COB | 14 W 4000 K



- ceiling recessed luminaire complx.100 rim
- with a rim projecting over the ceiling
- for installation into suspended ceilings
- with LED COB 2000 lm
- colour temperature: 4000 K
- colour rendering index: CRI >90
- L90 / B10 (50.000h) SDCM < 2
- net luminous flux: 1260 lm
- total load: 14 W
- luminous efficacy: 90,0 lm/W
- rotationsymmetrical light distribution, wide flood
- darklight reflector of aluminium, mirror finish anodised
 cut of angle: 40 °
- beam angle: 69 °
- UGR: 19
- with external LED power unit, electronic, 220-240 V, 0/50/60 Hz
- power supply: supply cord with plug connection 2x5x2,5 mm², length: 360 mm
- housing of die cast aluminium
- height: 125 mm
- diameter: 130 mm, recessing diameter: 120 mm
- recessing depth: 135 mm, ceiling thickness: 2-25mm
- weight: 0,86 kg
- protection rating: IP44
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: white (RAL9016)
- 108 742 04 910 R
- Overview of accessories on the following page / s

HOFFMEISTER

108 742 04 910 R **accessory**

Optional accessories

description accessory general	dimensions in mm	item number	picNo.
housing for concrete cast for recessed downlights complx.100 rim	ØxH: 342 x 160	108 605 10 000	01

01			