




## 108 744 03 910 R | white

complx.100 | rim  
ceiling recessed luminaire  
LED COB | 26 W 3000 K



- ceiling recessed luminaire complx.100 rim
- with a rim projecting over the ceiling
- for installation into suspended ceilings
- with LED COB 3000 lm
- colour temperature: 3000 K
- colour rendering index: CRI >90
- L90 / B10 (50.000h)
- SDCM < 2
- net luminous flux: 2080 lm
- total load: 26 W
- luminous efficacy: 80,0 lm/W
- rotationsymmetrical light distribution, flood
- darklight reflector of aluminium, mirror finish anodised
- cut of angle: 40 °
- UGR: 16
- with external LED power unit, electronic, 220-240 V, 0/50/60 Hz
- power supply: supply cord with plug connection 2x5x2,5 mm², length: 360 mm
- housing of die cast aluminium
- height: 115 mm
- diameter: 130 mm, recessing diameter: 120 mm
- recessing depth: 125 mm, ceiling thickness: 2-25mm
- weight: 0,86 kg
- protection rating: IP44
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: white (RAL9016)
- 108 744 03 910 R

- Overview of accessories on the following page / s

108 744 03 910 R  
**accessory****Optional accessories**

description accessory general	dimensions in mm	item number	pic.-No.
housing for concrete cast for recessed downlights complx.100 rim	ØxH: 342 x 160	108 605 10 000	01

01