


## 108 745 04 910 R | white

complx.100 | rim ceiling recessed luminaire LED COB | 26 W 4000 K



- ceiling recessed luminaire complx.100 rim
- with a rim projecting over the ceiling
- for installation into suspended ceilings
- with LED COB 3000 lm
- colour temperature: 4000 K
- colour rendering index: CRI >90
- L90 / B10 (50.000h) SDCM < 2
- net luminous flux: 1990 lm
- total load: 26 W
- luminous efficacy: 76,5 lm/W
- rotationsymmetrical light distribution, wide flood
- darklight reflector of aluminium, mirror finish anodised
- cut of angle: 40 °
- UGR: 20
- with external LED power unit, electronic, 220-240 V, 0/50/60 Hz
- power supply: supply cord with plug connection
   2x5x2,5 mm<sup>2</sup>, length: 360 mm
- housing of die cast aluminium
- height: 115 mm
- diameter: 130 mm, recessing diameter: 120 mm
  recessing depth: 125 mm, ceiling thickness: 2-25mm
- weight: 0,86 kg
- protection rating: IP44
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: white (RAL9016)
- 108 745 04 910 R

- Overview of accessories on the following page / s

## 108 745 04 910 R accessory

## Optional accessories

description accessory general	dimensions in mm	item number	picNo.
housing for concrete cast for recessed downlights complx.100 rim	ØxH: 342 x 160	108 605 10 000	01

01