





109 101 03 910 R | white

complx.150 | IP65
ceiling recessed luminaire
LED | 28 W 3000 K



- ceiling recessed luminaire complx.150 IP65
- with a rim projecting over the ceiling
- for installation into suspended ceilings
- with LED 2400 lm
- colour temperature: 3000 K
- colour rendering index: CRI >90
- L90 / B10 (50.000h)
- SDCM < 2
- net luminous flux: 1930 lm
- total load: 28 W
- luminous efficacy: 68,9 lm/W
- rotationsymmetrical light distribution, spot
- safety cable for reflector module
- darklight reflector of aluminium, mirror finish anodised
- cut of angle: 30 °
- beam angle: 10 °
- UGR: -8
- with external LED power unit, electronic, 220-240 V, 0/50/60 Hz
- power supply: push-wire terminal 2x5x2,5 mm²
- with IP68 cable gland
- housing of die cast aluminium
- safety glass, clear
- recessing ring of die cast aluminium
- height: 156 mm
- diameter: 190 mm, recessing diameter: 174 mm
- recessing depth: 161 mm, ceiling thickness: 4-35 mm
- weight: 3,3 kg
- protection rating: IP65
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: white (RAL9016)
- 109 101 03 910 R

- - -