
## **HOFFMEISTER**





## 112 260 14 910 I white

gin.o 2 Contour spotlight LED | 14 W 4000 K



- Contour spotlight gin.o 2
- with 3 circuit universal adapter
- for Hoffmeister control.x tracks
- circuit selection is possible while adapter is inserted into the track
- passive thermo management
- with LED 1560 lm
- colour temperature: 4000 K
- colour rendering index: CRI >80
- L90 / B10 (50.000h)
- SDCM < 2
- total load: 14 W
- Contour spotlights
- fresnel lense, glass-lens focusable
- LED power unit integrated in adapter, electronic (POTI), 220-240 V, 0/50/60 Hz - amplitude dimming
- adapter with integrated potentiometer dimming range: 100-1,4 %
- housing of die cast aluminium
- adapter of fibreglass reinforced thermoplastic framing attachment with holder metal, black
- length: 221 mm, width: 52 mm
- rotatable 360°, 90° tiltable
- weight: 1,41 kg
- protection rating: IP20
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany maximum ambient temperature: 35 ° C
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: white (RAL9016)
- 112 260 14 910

- - -