

<u>LED 3000K 2800lm</u> ≪14 221 39 L2500 cd/klr 58 **⊲**14° CO Ø[m] 0.25 0.51 0.76 1.01 1.26 h [m] 1.0 2.0 3.0 4.0 5.0 Em [lx] P 2347 587 260 146 84

113 342 03 906 D | silver

lo.nely 3 spotlight LED | 41 W 3000 K



- spotlight lo.nely 3
- with 3 circuit DALI adapter
- for Hoffmeister control.x tracks
- circuit selection is possible while adapter is inserted into the track
- passive thermo management
- with LED 3300 lm
- colour temperature: 3000 K
- colour rendering index: CRI >90
- L90 / B10 (50.000h)
- SDCM < 2
- net luminous flux: 2800 lm
- total load: 41 W
- luminous efficacy: 68,3 lm/W
- rotationsymmetrical light distribution, spot
- beam angle: 15 °
- LED power unit integrated in adapter, electronic (DALI)
- temperature-controlled LED circuit board (NTC)
- amplitude dimming
- dimming range: 100-1 %
- housing of die cast aluminium
- adapter of fibreglass reinforced thermoplastic
- microprismatic filter with very high rate of light transmission
- length: 221 mm, width: 84 mm, height: 197 mm
 rotatable 360°, 90° tiltable (can be fixed)
- weight: 1,25 kg
- protection rating: IP20
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- maximum ambient temperature: 35 ° C
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: silver
- 113 342 03 906 D

- - -

113 342 03 906 D accessory

Required accessories

description accessory general	dimensions in mm	item number	picNo.
antiglare flaps for spotlights gin.o and lo.nely size 3		105757	01

