
HOFFMEISTER







12500 CO/KUD + H0F10864			
LED 2	700K 2460lm	<14°	
h	CO	Em	
[m]	Ø[m]	[lx]	
1.0	0.25	20628	
2.0	0.51	5157	
3.0	0.76	2292	
4.0	1.01	1289	
5.0	1.26	825	

11334212 721-PA | black

lo.nely 3 spotlight LED | 41 W 2700 K



- spotlight lo.nely 3
- with recessed mounting plate
- for recessed installation into wall or ceiling
- passive thermo management
- with LED 2900 lm
- colour temperature: 2700 K
- colour rendering index: CRI >90 L90 / B10 (50.000h)
- SDCM < 2
- net luminous flux: 2460 lm
- total load: 41 W
- luminous efficacy: 60,0 lm/W
- rotationsymmetrical light distribution, spot
- beam angle: 15 °
- with external LED power unit, electronic
- temperature-controlled LED circuit board (NTC)
 power supply: supply cord with plug connection 2x5x2,5 mm², length: 360 mm
- suitable for through wiring
- housing of die cast aluminium
- microprismatic filter with very high rate of light transmission
- ceiling plate of die cast aluminium
- diameter: 96 mm, recessing diameter: 83 mm
- recessing depth: 103 mm, ceiling thickness: 1-45 mm rotatable 360°, 90° tiltable (can be fixed)
- weight: 1,4 kg
- protection rating: IP20
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- maximum ambient temperature: 35 ° C
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: black
- 11334212 721-PA

- - -

HOFFMEISTER

11334212 721-PA **accessory**

Required accessories

description accessory general	dimensions in mm	item number	picNo.
antiglare flaps for spotlights gin.o and lo.nely size 3		105757	01

