
HOFFMEISTER







	/~0000 QU/ NU	D=\ 1101 10003
LED 3	000K 2920lm	⊄ 23°
h	CO	Em
[m]	Ø[m]	[lx]
1.0	0.41	10090
2.0	0.81	2523
3.0	1.22	1121
4.0	1.63	631
5.0	2.03	404

113 343 03 910 D I white

lo.nely 3 spotlight LED | 41 W 3000 K



- spotlight lo.nely 3
- with 3 circuit DALI adapter
- for Hoffmeister control.x tracks
- circuit selection is possible while adapter is inserted into the track
- passive thermo management
- with LED 3300 lm
- colour temperature: 3000 K
- colour rendering index: CRI >90
- L90 / B10 (50.000h)
- SDCM < 2
- net luminous flux: 2920 lm
- total load: 41 W
- luminous efficacy: 71,2 lm/W
- rotationsymmetrical light distribution, medium
- beam angle: 25 °
- LED power unit integrated in adapter, electronic (DALI)
- temperature-controlled LED circuit board (NTC)
- amplitude dimming
- dimming range: 100-1 %
- housing of die cast aluminium
- adapter of fibreglass reinforced thermoplastic
- safety glass, clear
- length: 221 mm, width: 84 mm, height: 197 mm
- rotatable 360°, 90° tiltable (can be fixed)
- weight: 1,25 kg
- protection rating: IP20
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- maximum ambient temperature: 35 ° C
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: white (RAL9016)
- 113 343 03 910 D

_ _

HOFFMEISTER

113 343 03 910 D **accessory**

Required accessories

description accessory general	dimensions in mm	item number	picNo.
antiglare flaps for spotlights gin.o and lo.nely size 3		105757	01

