
HOFFMEISTER







7-29000 CU/KIIII-F HUF1086/			
LED 3	000K 2920lm	<110°	
h	CO	Em	
[m]	Ø[m]	[lx]	
1.0	0.18	47545	
2.0	0.36	11886	
3.0	0.54	5283	
4.0	0.71	2972	
5.0	0.89	1902	

11334713 906-PA | silver

lo.nely 3 spotlight LED | 41 W 3000 K



- spotlight lo.nely 3
- with recessed mounting plate
- for recessed installation into wall or ceiling
- passive thermo management
- with LED 3300 lm
- colour temperature: 3000 K
- colour rendering index: CRI >90 L90 / B10 (50.000h)
- SDCM < 2
- net luminous flux: 2920 lm
- total load: 41 W
- luminous efficacy: 71,2 lm/W
- rotationsymmetrical light distribution, spot
- beam angle: 10 °
- with external LED power unit, electronic
- temperature-controlled LED circuit board (NTC)
 power supply: supply cord with plug connection 2x5x2,5 mm², length: 360 mm
- suitable for through wiring
- housing of die cast aluminium
- safety glass, clear
- ceiling plate of die cast aluminium
- diameter: 96 mm, recessing diameter: 83 mm
- recessing depth: 103 mm, ceiling thickness: 1-45 mm
- rotatable 360°, 90° tiltable (can be fixed)
- weight: 1,4 kg
- protection rating: IP20
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- maximum ambient temperature: 35 ° C
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: silver
- 11334713 906-PA

HOFFMEISTER

11334713 906-PA **accessory**

Required accessories

description accessory general	dimensions in mm	item number	picNo.
antiglare flaps for spotlights gin.o and lo.nely size 3		105757	01

