
HOFFMEISTER







	12000 bd/k	Im + H0F13178
LED 2	700K 560lm	∢ 16°
h	CO	Em
[m]	Ø[m]	[lx]
1.0	0.29	3894
2.0	0.58	973
3.0	0.86	433
4.0	1.15	243
5.0	1.44	156

119 503 02 721 | black

car.a pendant luminaire LED | 10 W 2700 K



- pendant luminaire car.a
- with canopy
- for surface mounted ceiling installation
- with LED 700 lm
- colour temperature: 2700 K
- colour rendering index: CRI >90
- L80 / B10 (50.000h) SDCM < 2
- net luminous flux: 560 lm
- total load: 10 W
- luminous efficacy: 56,0 lm/W
- rotationsymmetrical light distribution, spot
- beam angle: 16 ° UGR: -4
- build in LED power unit, electronic, 220-240 V, 50/60 Hz
- Dimming with external dimmers possible (trailing-edge and leading-edge)
- power supply: supply cord 3x0,75 mm², length: 2000 mm
- housing of aluminium
- microprismatic filter with very high rate of light transmission
- height: 400 mm
- diameter: 65 mm, suspension length: 2500 mm
- weight: 1,926 kg
- protection rating: IP20
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: black
- 119 503 02 721