

HOFFMEISTER







LED 7	000K 530lm	∢39
LED 9	UUUK SSUIII	<10
h	CO	Е
[m]	Ø[m]	[t
1.0	0.71	74
2.0	1.42	18
3.0	2.14	8
4.0	2.85	L
5.0	3.56	3

119 505 03 721 | black

car.a pendant luminaire LED | 10 W 3000 K



- pendant luminaire car.a
- with canopy
- for surface mounted ceiling installation
- with LED 800 lm
- colour temperature: 3000 K
- colour rendering index: CRI >90
- L80 / B10 (50.000h) SDCM < 2
- net luminous flux: 530 lm
- total load: 10 W
- luminous efficacy: 53,0 lm/W
- rotationsymmetrical light distribution, flood
- beam angle: 40 ° UGR: 14
- build in LED power unit, electronic, 220-240 V, 50/60 Hz
- Dimming with external dimmers possible (trailing-edge and leading-edge)
- power supply: supply cord 3x0,75 mm², length: 2000 mm
- housing of aluminium
- microprismatic filter with very high rate of light transmission
- height: 400 mm
- diameter: 65 mm, suspension length: 2500 mm
- weight: 1,56 kg
- protection rating: IP20
- protection class I
- 5 years Hoffmeister warranty
- Made in Germany
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- colour: black
- 119 505 03 721