



1775965NW70D | black

177 | BLACK EDITION Arealflooter LED | 965 W 4000 K



- Arealflooter 177 BLACK EDITION
- for surface mounted installation on wall or ceiling
- mounting bracket must be ordered seperately
- with LED 155900 lm
- colour temperature: 4000 K
- colour rendering index: CRI >70
- L90 / B10 (100.000 / ta 25°C)
- net luminous flux: 117700 lm
- total load: 965 W
- luminous efficacy: 122,0 lm/W
 asymmetrical light distribution
- 5 integrated LED power units, electronic (DALI), 220-240 V, 0/50/60 Hz - overvoltage protection 10kV; discharge current 5kA
- dimmable 10-100%
- Number of luminaires per fuse (B16): 1
- power supply: plug connector angled 90° RST 20i5 5x2,5 mm²
- Optional loop-in loop-out cabling
- housing of aluminium and die cast aluminium
- safety glas, clear, partially ceramic printed
 length: 900 mm, width: 830 mm, height: 170 mm
- windage area: 0,75 m²
- weight: 43,6 kg
- protection rating: IP65
- protection class I
- 5 years Hoffmeister warranty
- designed and manufactured in Germany
- minimum ambient temperature: -40 ° C
- maximum ambient temperature: 40 ° C
- impact resistance class: IK10
- certificates: manufactured according to DIN VDE 0711 / EN 60598
- colour: black
- 1775965NW70D

- Overview of accessories on the following page / s

1775965NW70D accessory

Required accessories

description accessory general	dimensions in mm	item number	picNo.
Ceiling fixation for series 177		817700200	01
Mounting bracket, traverse mounting for series 177		817700300	02
Mounting bracket, for wall mounting		817700400	03

