








| OOK          | - 00.0 |       |
|--------------|--------|-------|
| E[lx]        | 100lx  | 500lx |
| a[m²]<br>100 | n=5    | n=23  |
|              |        |       |

## 81535040NW-US

453/454 LED Upgrade Kit LED | 40 W 4000 K



- LED Upgrade Kit 453/454
- to plane projector 153/154
- with LED 5200 lm
- colour temperature: 4000 K
- colour rendering index: CRI >80
- SDCM < 3
- net luminous flux: 3570 lm
- total load: 40 W
- luminous efficacy: 89,3 lm/W
- asymmetrical light distribution, deep with built in LED power unit, electronic (DALI), 220-240 V, 0/50/60 Hz
- overvoltage protection 6KV
- optional DC voltage suitable (AC/DC) 15% power for operation in emergency lighting systems
- further dimming functions on request
- amplitude dimming
- power supply: connecting terminal 5x2,5 mm²
  Glass replacementment recomended (article number glass: 8153000100)
- length: 444 mm, width: 282 mm, height: 104 mm
- windage area: 0,04 m²
- weight: 2,16 kg
- protection class I
- 5 years warranty
- designed and manufactured in Germany
- maximum ambient temperature: 40 ° C
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- 81535040NW-US
- Overview of accessories on the following page / s



## 81535040NW-US accessory

## Optional accessories

| description accessory general               | dimensions in mm | item number | picNo. |
|---|------------------|-------------|--------|
| Replacement glass with hinge, seal included |                  |             | _      |
| for upgrade kit 453/454                     |                  | 8153000100  | 01     |

