



## 81539040WW-US

453/454  
LED Upgrade Kit  
LED | 40 W 3000 K



- LED Upgrade Kit 453/454
- to plane projector 153/154
- with LED 5510 lm
- colour temperature: 3000 K
- colour rendering index: CRI >80
- SDCM < 3
- net luminous flux: 4240 lm
- total load: 40 W
- luminous efficacy: 106,0 lm/W
- bidirectional light distribution
- with built in LED power unit, electronic (DALI), 220-240 V, 0/50/60 Hz
- overvoltage protection 6KV
- optional DC voltage suitable (AC/DC) - 15% power for operation in emergency lighting systems
- further dimming functions on request
- amplitude dimming
- power supply: connecting terminal 5x2,5 mm²
- Glass replacement recommended (article number glass: 8153000100)
- length: 444 mm, width: 282 mm, height: 104 mm
- windage area: 0,04 m²
- weight: 1,3 kg
- protection class I
- 5 years warranty
- designed and manufactured in Germany
- maximum ambient temperature: 40 °C
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- 81539040WW-US

- Overview of accessories on the following page / s

81539040WW-US

**accessory****Optional accessories**

description accessory general	dimensions in mm	item number	pic.-No.
Replacement glass with hinge, seal included for upgrade kit 453/454		8153000100	01

