


| LED 3000 | 700 cd.4 | BOOLM | > |
|--|----------|--------------|---|
| <u>LED 3000</u> η _{LOR} = UGR = | 100% | 600lm | |
| <u>E[lx]</u> a[m²] | 100lx | 500lx n=4 | - |

81555240WW-US

455 LED Upgrade Kit LED | 240 W 3000 K



- LED Upgrade Kit 455 to plane projector 155 with LED 34000 lm

- colour temperature: 3000 K - colour rendering index: CRI >80
- SDCM < 3 - net luminous flux: 28600 lm
- total load: 240 W
- luminous efficacy: 119,2 lm/W
- asymmetrical light distribution, deep
 with built in LED power unit, electronic (DALI),
- with balt in EED power dnit, electionic (DEE),
 220-240 V, 0/50/60 Hz
 overvoltage protection 10KV
 optional DC voltage suitable (AC/DC) 15% power for operation in emergency lighting systems - further dimming functions on request
- amplitude dimming
- Glass replacementment recomended (article number glass: 8155000100)
- length: 703 mm, width: 420 mm, height: 150 mm
- windage area: 0,10 m²
 weight: 3,9 kg
- protection class I
- 5 years Hoffmeister warranty
 designed and manufactured in Germany
- certificates: manufactured according to DIN VDE 0711 / EN 60598, CE
- 81555240WW-US

- - -

81555240WW-US accessory

Required accessories

| description accessory general | dimensions in mm | item number | picNo. |
|---|------------------|-------------|--------|
| Replacement glass with hinge, seal included for upgrade kit 455 | | 8155000100 | 01 |

